



SECTION A-A

$A_o = 12.35 \text{ mm}$
 $B_o = 12.35 \text{ mm}$
 $K_o = 1.65 \text{ mm}$
 $K_1 = 1.15 \text{ mm}$

- All Dimensions in Millimeters -

Notes:

1. 10 sprocket hole pitch cumulative tolerance ± 0.2
2. Camber not to exceed 1mm in 100mm
3. Material: Conductive Black Advantek Polystyrene
4. A_o and B_o measured on a plane 0.3mm above the bottom of the pocket
5. K_o measured from a plane on the inside bottom of the pocket to the top surface of the carrier.
6. Pocket position relative to sprocket hole measured as true position of pocket, not pocket hole.

TOLERANCES (EXCEPT AS NOTED)	REVISIONS				Advantek Part Number Q1010P-D Carrier Tape			
	NO.	DESCRIPTION	DATE	BY				
DECIMAL	1				<div style="font-size: 2em; font-weight: bold; margin-bottom: 10px;">A</div> DRAWN BY: SDC/BTH SCALE: 1 inch = 10mm REFERENCE NO: DATE: 9/5/97 MATERIAL: see Note 3 DRAWING NO. A0905-97-1 REV:			
± 0.1	2							
FRACTIONAL	3							
\pm	4							
ANGULAR	5							